



Comfort-Line Pressing Unit ACO401

Highly Efficient Powerhouse

- High press force - powerful for large pipe dimensions
- Ideally suitable for special applications with special requirements concerning high pressure
- Battery status indicator - Battery capacity can be controlled anytime



Metal up to
168.3 mm



Rechargeable
battery



Rotatable head

Press collar HP 401



novopress
because quality matters

Efficient press technology

The Comfort-Line Pressing Unit ACO401 is ideal for high-pressure applications with dimensions from 76.1 to 108.0 mm and for drinking water installations even up to 168.3 mm. In comparison to conventional welding connections, this pressing unit enables a time saving up to 90 %.

Scope of application

- Drinking water-, gas- and heating installations, industry and commercial applications and many more
- Availability of jaws suitable for M-Profile fittings of various manufacturers in the market*

Accessories

- Press collars 401
- Charger available in many worldwide power supply specifications
- 18 V Milwaukee batteries with implemented battery-status-indication available



Strong connection in a short time.

Novopress quality and service

Comfort-Line

- Battery-empty-detection
- Error display
- Device information through the LED indication under the start button
- Automatic pressing cycle

Maintenance and service

- Qualified service on site thanks to international service network
- Mobile on-site service thanks to our service vehicle in Germany and parts of Europe
- Extended warranty (further information at www.novopress.de)

Technical Data ACO401

Dimensions:	Metal pipe up to 76.1 / 88.9 / 108.0 / 114.0 / 139.7 / 168.3 mm, further on request
Weight incl. Battery:	13 kg
Length:	660 mm
Width:	100 mm
Height:	250 mm
Power consumption:	450 W
Piston force:	100 kN
Piston stroke:	60 mm
Battery:	18 V / 3.0 Ah Li-Ion Milwaukee
Battery capacity:	15 - 20 press cycles
Charging time:	ca. 60 min.

* for binding information please request your system manufacturer

We reserve the right to make technical modifications.

novopress

Novopress GmbH & Co. KG
Scharnhorststraße 1 · D-41460 Neuss
Tel.: +49(0)2131-288-0 · Fax: +49(0)2131-288-55
www.novopress.de · E-Mail: verkauf@novopress.de